



VITAFLOW

VF # 1802-10\"/>

6\"/>

Materials

Body	Carbon Steel
Diffuser	Carbon Steel
Nozzle	Monel or 316 SS
Fasteners	316 Stainless Steel
Coating	Epoxy Paint
Throat Liner	Optional
Gaskets:	Neoprene

Operating Data

Suction Capacity	900-2900 GPM
Inlet Pressure	75-175 PSI
Inlet Quantity	900-2300 GPM
Suction Lift	Up to -20 Feet
Discharge Head	Up to 100 Feet

Client:

Service:	Bilge / Ballast
Agent:	
Location	
Ref NO:	
VM Part #	VM1524560
Drawing #	A-VM15560 Rev. A
VM Ref #	15560-9570210LF

DIMENSION DATA

FLANGE DATA: 150 lb ANSI B16.24 Flat Face (or DIN or JIS)

A	B	C	D		ID	OD	# Holes	BC	Hole Ø
70½"	62½"	8"	10"	Inlet	6"	11"	8	9½"	7/8"
				Suction	10"	16"	12	14¼"	1"
				Discharge	10"	16"	12	14¼"	1"

Dimensions are approximate. Final dimensions to be confirmed at time of order placement.

VITAFLOW, LLC, 576 N. Birdneck Rd, Unit 142, Virginia Beach, VA 23451, Michael Hume, COO, Ph: 904/316-5774, mhume@vitaflow.com