

VITAFLOW 925-N-2½"L

Bilgemate Multi-jet Nozzle

Materials of Construction:

Body & Diffuser Bronze ASTM B 62
Nozzle Monel or 316 Stainless

Flange Connections:

All flanges 150 lb. ANSI B16.24 Flat Face
Also available with DIN or JIS flanges

Dimensions:

	<u>Inches</u>	<u>Millimeters</u>
Inlet	1½"	40
Suction	2½"	65
Discharge	2½"	65
"A"	21"	533
"B"	3¼"	82
"C"	17.75"	451
"D"	5"	127
Weight	70 lbs.	32 kg

General Specifications:

- Suction Capacity Up to 180 GPM
- Suction Lift Up to -20 Feet)
- Discharge Head Up to 100 Ft.
- Inlet Quantity Up to 250 GPM)
- Inlet Pressure Up to 150 PSI

BILGEMATE Peripheral –Jet nozzle eductor has a straight through suction path for non-clog flow of liquids mixed with solid materials and slurries.

Notes:

1. Throat size varies up to ½" diameter
2. Available with threaded connections
3. Spare replacement nozzles available
4. Eductor is furnished to meet the Requirements of each application
5. Optional replaceable throat wear Sleeve lining in ceramic or stainless
6. Shock & Vibration Tested & Approved for U.S. Navy applications

V.F. 925-N-2½"L Bilgemate

VITAFLOW, LLC,
576 N. Birdneck Rd, Unit 142,
Virginia Beach, VA 23451,
Michael Hume, COO,
Ph: 904/316-5774, mhume@vitaflow.com

